



BD852L

The 1¾-in. (45 mm) wide tool belt is a tongue and buckle tool belt that is constructed to allow the accommodation of pouches or other tool carrying accessories without deformation or collapse.

For further information, refer to "Use and Maintenance Instructions" for harnesses, belts and lanyards.

⚠ WARNING

Since January 1st, 1998, waist belts have been prohibited for fall arrest. A full body harness must be used.

Features

- Tongue and buckle attachment
- Compatible with all Tractel harnesses
- Large side D-rings on work positioning model (BD852)
- Large single back D-ring on restraint model (BD842)

Sizes

Small	31 – 39 in.	(78 – 100 cm)	BD852 S
Medium	35 – 43 in.	(88 – 110 cm)	BD852 M
Large	38 – 46 in.	(98 – 120 cm)	BD852 L
X-large	44 – 52 in.	(108 – 130 cm)	BD852 XL
XX-large	48 – 56 in.	(122 – 142 cm)	BD852 XXL

Applicable standards

- ANSI Z359.1-1999 and A10.32-2004
- OSHA fall protection requirements
- CSA Z259.1-05

Available models

- BD832 Tool belt without D-ring
BD842 Single back D-ring for travel restraint applications
BD852 Side positioning D-rings for work positioning

PARTS	SPECIFICATIONS	APPLICABLE STANDARDS
Webbing	High tenacity polyester Width: 1¾ in. (45 mm) Thickness: ¼ in. (3 mm) Tensile strength: 8,500 lbs. (37.8 kN) Webbing is heat-cut to prevent fraying.	ANSI Z359.1-1999 CSA Z259.1-05
Stitching	Belt is lock-stitched. Thread: #207 polyester	CSA Z259.12-01
Back and side D-ring	Plating: zinc dichromate Proof loaded 100% at 3,600 lbs. (16 kN) Tensile strength: 5,000 lbs. (22.2 kN) general rating	ANSI Z359.1-1999 CSA Z259.12-01
Tongue & buckle	Plating: zinc dichromate Tensile strength: 5,000 lbs. (22.2 kN)	ANSI Z359.1-1999 CSA Z259.12-01
Grommets	#2 spur brass	CSA Z259.12-01
Elastic belt keeper	To secure tail end of belt	CSA Z259.1-05
Capacity	310 lbs. (140 kg), one person	ANSI Z359.1 CSA Z259.1-05