

**BD952L**

This Thermal-formed padded belt is specially designed for positioning or restraint applications. It is ideal for use with the Tractel Versafit of Ultra-light harnesses. The tongue and buckle tool belt is constructed to allow the accommodation of pouches or other tool carrying accessories without deformation or collapse.

For further information, refer to "Use and Maintenance Instructions" for harnesses, belts and lanyards.

**⚠ WARNING**

Since January 1<sup>st</sup>, 1998, waist belts have been prohibited for fall arrest. A full body harness must be used.

**Features**

- Tongue and buckle attachment
- High support
- Compatible with all Tractel harnesses
- Large D-ring(s) on models BD942 and BD952
- Removable tool belt for tool pouch attachment

**Sizes**

Small	31 – 39 in. (78 – 100 cm)	<b>BD952S</b>
Medium	35 – 43 in. (88 – 110 cm)	<b>BD952M</b>
Large	38 – 46 in. (98 – 120 cm)	<b>BD952L</b>
X-large	44 – 52 in. (108 – 130 cm)	<b>BD952XL</b>
XX-large	48 – 56 in. (122 – 142 cm)	<b>BD952XXL</b>

**Applicable standards**

- ANSI Z359.1-1999 and A10.32-2004
- OSHA fall protection requirements
- CSA Z259.1-05

**Available models**

- BD932    Removable tool belt without D-ring  
BD942    Single back D-ring for travel restraint applications  
BD952    Side positioning D-rings for work positioning

# technical sheet

## Thermal-formed padded belt

ref.: T-4508  
rev. no.: 6  
date: 02/07  
page: 2/2

PARTS	SPECIFICATIONS	APPLICABLE STANDARDS
Belt webbing	High tenacity polyester Width: 1¼ in. (45 mm) Thickness: ½ in. (3 mm) Tensile strength: 8,500 lbs. (37.8 kN) Webbing is heat-cut to prevent fraying.	ANSI Z359.1-1999 CSA Z259.1-05
Back support foam	Closed cell foam laminate Thickness: ⅜ in. (8 mm)	
Stitching	Belt is lock-stitched. Threads: #207 polyester	CSA Z259.12-01
Back or side D-ring	Plating: zinc dichromate Proof loaded 100% at 3,600 lbs. (16 kN) Tensile strength: 5,000 lbs. (22.2 kN) general rating	ANSI Z359.1-1999 CSA Z259.12-01
Tongue and buckle	Plating: zinc dichromate Tensile strength: 4,000 lbs. (17.8 kN)	ANSI Z359.1-1999 CSA Z259.12-01
Grommets	#2 spur brass	CSA Z259.12-05
Elastic belt keeper	To secure tail end of belt.	CSA Z259.1-05
Capacity	310 lbs. (140 kg), one person	ANSI Z359.1-1999 CSA Z259.1-05