

AC732

The Versafit harness is Tractel®'s most versatile harness. With its adjustable leg, shoulder, chest and sub-pelvic straps it can be adjusted to a perfect fit for maximum comfort.

For further information, refer to "Use and Maintenance Instructions" for harnesses, belts and lanyards.

Features

- Adjustable sub-pelvic strap
- Seven-point adjustment
- Adjustable back D-ring
- Adjustable chest strap
- Lanyard retaining clips on both shoulder straps
- Fall indicators / inspection tag / serial number
- Accommodates tool belt up to 4 in. (102 mm) wide
- Ideal for use with Tracvest
- Two colors: blue shoulder straps and black leg straps

Sizes

- One size: AC732 (fits most)
- Small: AC732S
- X-large: AC732XL
- XX-large: AC732XXL


Applications

- Fall arrest
- Optional:
 - work positioning
 - retrieval
 - ladder climbing
 - suspension

Applicable standards

- CSA Z259.10-06

AVAILABLE MODELS




Tongue and buckle style

AC732 – Quick connect legs
AD732 – Tongue and buckle legs



- Fall arrest attachment element (mandatory)
- Fall arrest applications




Side positioning D-rings

AC742 – Quick connect legs
AD742 – Tongue and buckle legs



- Side positioning D-rings
- Fall arrest and work positioning applications




Side positioning and frontal attachment

AC7122 – Quick connect legs
AD7122 – Tongue and buckle legs



- Side positioning and frontal attachment
- Fall arrest, work positioning, descent and ladder climbing application




Shoulder retrieval D-rings

AC752 – Quick connect legs
AD752 – Tongue and buckle legs



- Shoulder retrieval D-rings
- Fall arrest and retrieval applications




Side positioning and shoulder retrieval D-rings

AC772 – Quick connect legs
AD772 – Tongue and buckle legs



- Side positioning and shoulder retrieval D-rings
- Fall arrest, work positioning and retrieval applications




Frontal attachment

AC762 – Quick connect legs
AD762 – Tongue and buckle legs



- Frontal attachment
- Fall arrest, descent and ladder climbing applications




Ladder harness

AC722 – Quick connect legs
AD722 – Tongue and buckle legs



- Upper sternum D-ring
- Fixed chest strap
- For fall arrest with ladder climbing




Scaffold harness

AC732/D – Quick connect legs
AD732/D – Tongue and buckle legs



- Shoulder pads
- Fixed chest strap
- For fall arrest and ladder climbing within scaffold environments

MODULAR CAPABILITY



Belt loops

The Versafit harness has belt loops to accommodate any Tractel® belts or your favorite tool belt which is up to 4 in. (102 mm) wide.

PARTS	SPECIFICATIONS	APPLICABLE STANDARDS
Standard webbing	High tenacity polyester Width: 1¾ in. (45 mm) Thickness: ¼ in. (1.4 mm) Tensile strength: 5,700 lbs. (25.4 kN) Webbing is heat-cut to prevent fraying.	CSA Z259.10-06 ANSI Z359.1-2007
Tongue and buckle webbing (legs)	High tenacity polyester Width: 1¾ in. (45 mm) Thickness: ¼ in. (3 mm) Tensile strength: 10,000 lbs. (44.5 kN) Webbing is heat-cut to prevent fraying.	CSA Z259.10-06 ANSI Z359.1-2007
Stitching	Harness is lock-stitched. Thread: #138 polyester	CSA Z259.12-01
Back and side D-ring	Plating: zinc dichromate Proof-loaded 100% at 3,600 lbs. (16 kN) Tensile strength: 5,000 lbs. (22.2 kN)	CSA Z259.12-01 ANSI Z359.1-2007
Sliding bar adjuster	Plating: zinc dichromate Tensile strength: 4,000 lbs. (17.8 kN)	CSA Z259.12-01 ANSI Z359.1-2007
Quick connect buckle	Plating: zinc dichromate Tensile strength: 4,000 lbs. (17.8 kN)	CSA Z259.12-01 ANSI Z359.1-2007
Tongue and buckle	Plating: zinc dichromate Tensile strength: 4,000 lbs. (17.8 kN)	CSA Z259.12-01 ANSI Z359.1-2007
Grommets	#2 spur brass	
Plastic and elastic retainers	Each webbing strap with a free end has keeper loops.	CSA Z259.10-06
Capacity	386 lbs. (175 kg), one person	CSA Z259.10-06